MAVERICK X® mr

HIGHLIGHTS

- 101-hp Rotax® 1000R V-twin engine with high-flow dynamics
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok[‡] QE auto-locking front differential
- Intelligent Throttle Control (iTC™)
- Continuously Variable Transmission (CVT) with Quick Response System (QRS)
- Mid-engine layout for mass centralization
- Double A-arm front suspension with 12 in. (30.5 cm) of travel
- Torsional Trailing A-arms (TTA) independent rear suspension with 12 in. (30.5 cm) of travel
- Front sway bar

- Front and rear FOX[†] 2.5 PODIUM QS3[†]
- 14-in. cast-aluminum wheels with 30-in. Gorilla Axle Silverback† tires
- Strategically positioned engine air intake and CVT inlets / outlets
- 4,500-lb (2,041 kg) winch
- · Extra low L-Gear
- Analog / Digital gauge
- Passenger handhold and grab bar
- X-package seat trims, graphics and sponsor decals



White, Black & Can-Am Red / 1000R Hyper Silver, Black & Octane Blue / 1000R

| ENGINE | 1000R |
|----------------------|---|
| Туре | 101 hp, Rotax 976 cc, V-twin, liquid cooled with strategically positioned engine air intake |
| Fuel Delivery System | Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI) |
| Transmission | Quick Response System (QRS) CVT with high airflow, L / H / N / R / P, extra low L-Gear |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |

| BRAKES | |
|--------|--|
| Front | Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers |

| TIRES / WHEELS | |
|----------------|---|
| Front Tires | Gorilla Axle Silverback 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm) |
| Rear Tires | Gorilla Axle Silverback 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm) |
| Wheels | 14-in. cast-aluminum |

| DIMENSIONS / CAPACITIES | | |
|-------------------------|---|--|
| LxWxH | 118.8 x 67.9 x 76.2 in. (302 x 172 x 194 cm) | |
| Wheelbase | 84.3 in. (214.1 cm) | |
| Ground Clearance | 15 in. (38 cm) | |
| Dry Weight* | 1,323.8 lb (600 kg) | |
| Rack Capacity | 200 lb (91 kg) with LinQ™ quick-attach | |
| Storage Capacity | Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L) | |
| Towing Capacity | N/A | |
| Fuel Capacity | 10 gal (37.8 L) | |

| FEATURES | | | |
|----------|---|-------------------|--|
| Gauge | Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off | Protection | N/A |
| | | Instrumentation | Lighter type DC outlet in console, standard connector in the back (15-A) |
| | | Lighting | 240 W from four 60-W projectors with tail lights / brake lights |
| Winch | 4,500-lb (2,041 kg) winch with roller fairlead | Anti-theft System | Digitally Encoded Security System (D.E.S.S.™) |

| WARRANTY | |
|----------|-----------------------------------|
| Factory | 6-months limited warranty |
| Extended | Up to 30 months B.E.S.T. coverage |



