# amaverick x3 x ds turbo r

# HIGHLIGHTS

# DEFIANT

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with fourway adjustable seats

# **POWERFUL**

- Industry leading 172 hp turbocharged and intercooled Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

# PRECISE

- TTX suspension with industry leading travel
- Ultra efficient and
- lightweight chassis
- Sharpest handling features



Platinum Satin / TURBO R Triple Black / TURBO R

# Circuit Yellow / TURBO R

# SPECIFIC TO X ds PACKAGE

- 14-in. aluminum beadlock wheels with 29-in. Maxxis Bighorn<sup>†</sup> 2.0 tires
- Front and rear 20-in. suspension travel
- Fully adjustable FOX<sup>†</sup> 2.5 PODIUM RC2<sup>†</sup> Piggyback shocks
- Painted color options

ENGINE	TURBO R
Туре	172 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and Donaldson† high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Selectable 2WD / 4WD with Visco-Lok <sup>‡</sup> X auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)

TIRES / WHI	ELS
Front Tires	Maxxis Bighorn 2.0 29 x 9 x 14 in. (73.7 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 29 x 11 x 14 in. (73.7 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) aluminum beadlock

Front Suspension	Double A-arm with sway bar 20 in. (50.8 cm) travel			
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression and rebound adjustments			
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 20 in. (50.8 cm) travel			
Rear Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound adjustments and bottom-out control			
BRAKES				

DIMENSIONS /	CAPACITIES
LxWxH	131 x 64 x 66 in. (332.7 x 162.5 x 167.6 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Estimated Dry Weight	1,490 lb (675.9 kg)
Cage / Chassis	Dual-phase 980 steel, fully welded
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Center console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

FIOUI	Duai 262 mm venthated disc brakes with hydraulic twin-piston campers	
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers	
		Fuel Ca
FFATURES		

<b>FEATURES</b>			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	Integrated front bumper, full High Molecular Weight (HMW) skid plate and quarter-doors
		Instrumentation	Lighter type DC outlet in central console
		Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage



