amaverick x3 x rc Turbo

HIGHLIGHTS

DEFIANT

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with fourway adjustable seats

POWERFUL

- 120 hp turbocharged Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

PRECISE

- TTX suspension with industry leading travel
- Ultra efficient and
- lightweight chassis
- Sharpest handling features

SPECIFIC TO X rc PACKAGE

- 64-in. Wide
- Smart-Lok™* Full lockable on-the-fly front differential with electronically-controlled automatic modes
- 14-in. aluminum wheels with 30-in. Maxxis Liberty tires
- Front and rear 20 in. of suspension travel
- FOX† 2.5 PODIUM Piggyback shocks with QS3† compression adjustment
- Front bumper, heavy-duty full High Molecular Weight (HMW) skid plate with differential and under bumper skid plates, quarter-doors, UHMW rock sliders, front and rear suspension arm HMW protectors, 4,500-lb (2,041 kg) winch, front and rear tow hooks



Carbon Black & Octane Blue / TURBO

ENGINE	TURB0
Туре	120 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled and Donaldson† high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTCTM) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok™* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD ROCK / 4WD TRAIL
	*Smart-Lok™was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS			
Front Suspension	Double arched A-arm with sway bar 20-in. (50.8 cm) travel		
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment		
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched l links, 20-in. (50.8 cm) travel		
Rear Shocks	FOX† 2.5 PODIUM Piggyback with QS3†compression adjustment and bottom-out control		
BRAKES			
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers		

TIRES / WHEE	LS
Front Tires	Maxxis Liberty† 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Rear Tires	Maxxis Liberty† 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Wheels	14-in. (35.6 cm) aluminum

DIMENSIONS / CAPACITIES		
LxWxH	133 x 64 x 66 in. (337.8 x 162.5 x 167.6 cm)	
Wheelbase	102 in. (259.1 cm)	
Ground Clearance	14 in. (35.6 cm)	
Estimated Dry Weight	1,631 lb (739.8 kg)	
Cage / Chassis	Dual-phase 980 steel , fully welded	
Rack Capacity	200 lb (91 kg) with LinQ™ quick- attach	
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)"	
Fuel Capacity	10.5 gal (40 L)	

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto	Protection	Front bumper, heavy-duty full High Molecular Weight (HMW) skid plate with differential and under bumper skid plates, quarter-doors, UHMW rock sliders, front and rear suspension arm HMW protectors
	shut off	Instrumentation	Lighter type DC Outlet in central console
		Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500-lb (2,041 kg) winch with synthetic rope	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage





