SMAVERICK X3 X mr TURBO R

HIGHLIGHTS					
DEFIANT	POWERFUL PRECISE				
 Trademark Can-Am DN. next generation design Low seating position Ergo-Lok cockpit with fway adjustable seats 	A with • Industry leading 172 hp turbocharged and intercooled Rotax [®] ACE engine • TTX suspensio leading travel Ultra efficient	and assis			
SPECIFIC TO X mr PA	CKAGE				
Smart-Lok [™] * Full locka modes 14-in. aluminum beadl Up to 24-in. of suspens FOX ⁺ 2.5 PODIUM Piggy 4,500-lb (2,041kg) win	back shocks with QS3 ⁺ compression adjustment ch with synthetic rope Molecular Weight (HMW) skid plate, under bumper skid plat		Carbon Black & S	unburst Yellow / TURBO R	
ENGINE	TURBO R		TIRES / WHEEI	S	
Туре	172 hp, Rotax ACE (Advanced Combustion Efficien Turbocharged Triple-cylinder engine, liquid cooled wit intercooler, Donaldson† high-perfomance air filter and	cy) 900 cc th integrated	Front Tires	ITP Cryptid 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)	
	positioned engine air intake		Rear Tires	ITP Cryptid	
Fuel Delivery System Transmission	Intelligent Throttle Control (iTC [™]) with Electronic Fuel Injection (EFI) Quick Response System X (QRS-X) CVT, high airflow with strategically			30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)	
	positioned CVT air intakes and exhaust, L / H / N		Wheels	14-in. (35.6 cm) aluminum beadlock	
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry		DIMENSIONS / LxWxH	CAPACITIES 133 x 72 x 67 in. (337.8 x 182.9 x 170.2 cm)	
Power Steering Tri-Mode Dynamic Power Steering (DPS™)) —	Wheelbase	102 in. (259.1 cm)	
SUSPENSIONS			Ground Clearance	15 in. (38.1 cm)	
Front Suspension	Double arched A-arm with sway bar 22-in. (55.9 cm) travel / Trophy truck inspired arms		Estimated Dry Weight	1,689 lb (766.1 kg)	
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment		Cage / Chassis	Dual-phase 980 steel, fully welded	
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links, 24-in. (61 cm) travel		Rack Capacity	200 lb (91 kg) with LinQ [™] quick- attach	
Rear Shocks BRAKES	FOX† 2.5 PODIUM Piggyback with QS3†compression adjustment and bottom-out control		Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-	· ·	Fuel Capacity	10.5 gal (40 L)	
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-	piston calipers			
FEATURES					
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport / ECO™ mode, seat	Protection		Front bumper, full High Molecular Weight (HMW) skid plate, under bumper skid plate, half-doors, front and rear tow hooks	
	belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Instrumentation		r type DC Outlet in central console	
		Lighting		LED headlights and tail lights with unique Can-Am LED signature	
Winch	4,500-lb (2,041 kg) winch with synthetic rope	Anti-theft System	RF Digitally E	Encoded Security System (D.E.S.S.™) with Start/ Stop button	
WARRANTY					
		6 months limited wa	orranty		
Factory		6-months limited wa	nidilly		

Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage

©2017 Bombardier Recreational Products Inc (BRP). All rights reserved. ^{™M}, [®] and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A, the products are distributed by BRP US Inc. 'All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat beft at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years oid. Passenger must be at least 12 years oid and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.



Can-AmOffroad.com