§MAVERICK™ X3 MAX X™ ds TURBO R

HIGHLIGHTS

DEFIANT

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with front and rear four-way adjustable seats

POWERFUL

- Industry leading 172 hp turbocharged and intercooled Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

PRECISE

- TTX suspension with industry leading travel
- Ultra efficient and
- lightweight chassis
- Sharpest handling features



Platinum Satin / TURBO R Triple Black / TURBO R

Circuit Yellow / TURBO R

SPECIFIC TO X ds PACKAGE

- 14-in. aluminum beadlock wheels with 29-in. Maxxis Bighorn[†] 2.0 tires
- Front and rear 20-in. suspension travel
- Fully adjustable FOX[†] 2.5 PODIUM RC2[†] Piggyback shocks
- Painted color options

ENGINE	TURBO R
Туре	172 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and Donaldson† high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] X auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)

LIKES / WHEE	Lo
Front Tires	Maxxis Bighorn 2.0 29 x 9 x 14 in. (73.7 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 29 x 11 x 14 in. (73.7 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) aluminum beadlock

2025EN2ION	5
Front Suspension	

Front Suspension	Double A-arm with sway bar 20 in. (50.8 cm) travel			
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression and rebound adjustments			
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 20 in. (50.8 cm) travel			
Rear Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound adjustments and bottom-out control			

BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

LxWxH	162 x 64 x 65 in. (411.7 x 162.5 x 165.1 c
Wheelbase	135 in. (342.9 cm)
Ground Clearance	13 in. (33 cm)
Estimated Dry Weight	1,735 lb (786.9 kg)
0/01:-	Dual shace 000 steel fully

Estimated Dry Weight	1,735 lb (786.9 kg)
Cage / Chassis	Dual-phase 980 steel, fully welded
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Center console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)
Fuel Capacity	10.5 gal (40 L)

Gauge	Multifunction Analog / Digital:
	Speedometer, tachometer, odometer, trip and hour
	meters, fuel, gear position, sport / ECO™ mode, seat
	belt and 4 x 4 indicator, diagnostics, clock,
	auto shut off

Protection	Integrated front bumper, full High Molecular Weight (HMW) skid plate and quarter-doors		
Instrumentation	Lighter type DC outlet in central console		
Lighting	LED headlights and tail lights with unique Can-Am LED signature		
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button		

W		_		-	
	/ 1 / 1				 V 7 A

Winch

Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage

N/A

©2017 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Visco-Lok is a trademark of GKN Viscodrive GmbH. 'All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.



