©OUTLANDER™ MAX PRO 650 T3

HIGHLIGHTS

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Extra Low L gear
- Tri-Mode Dynamic Power Steering (DPS™)
- Torsional Trailing arm Independent rear suspension (TTI)
- Increased ground clearance
- 12-in. cast-aluminum wheels
- 26-in. 6-ply Carlisle[†] ACT HD radial tires
- · Relocated air intakes
- 1,361 kg WARN† winch with roller fairlead

- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- · Raised floorboards
- 21.4 L water-resistant rear compartment



Brushed Aluminum

ENGINES	650
Туре	Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE ⁺ auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm with increased suspension pre-load 22.9 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) with increased suspension pre-load 23.6 cm travel
Rear Shocks	Oil


BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	S
Front Tires	Carlisle [†] ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle [†] ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES			
LxWxH	238.8 x 116.8 x 135 cm		
Wheelbase	149.9 cm		
Ground Clearance	30.5 cm		
Seat Height	87.7 cm		
Dry Weight*	361 kg		
Rack Capacity	Front: 45 kg Rear: 90 kg		
Storage Capacity	Rear: 21.4 L		
Towing Capacity	750 kg trailer with brakes and 590 kg trailer without brakes		
Fuel Capacity	20.5 L		

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Seat with backrest
Winch	1,361 kg WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
T3 features	Seat with backrest, lockable fuel cap, transmission lockable in park mode (P), towing hitch and trailer plug, two front position lamps + directional indicators, extra tail light / brake light + directional		

WARRANTY	
Factory	2 years



indicators, mirrors, horn



