## **©OUTLANDER™ MAX XT 650™**

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg WARN† winch with roller fairlead
- Heavy-duty front and rear bumpers
- 14-in. cast-aluminum wheels
- 26-in. ITP<sup>†</sup> Terracross radial tires
- · Painted plastics for premium look
- · Handlebar wind deflectors
- Convertible Rack System (CRS) with LinQ™ system
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips

- · Raised floorboards
- 21.4 L water-resistant rear compartment
- 625-W magneto



Brushed Aluminum & Can-Am Red

ENGINES	650
Туре	62 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

Front Suspension	Double A-arm 22.9 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 23.6 cm travel
Rear Shocks	Oil

	22.9 cm travel	
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent (TTI) 23.6 cm travel	
Rear Shocks	Oil	
BRAKES		
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper	

TIRES / WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES		
LxWxH	238.8 x 116.8 x 135 cm	
Wheelbase	149.9 cm	
<b>Ground Clearance</b>	27.9 cm	
Seat Height	87.7 cm	
Dry Weight*	361 kg	
Rack Capacity	Front: 45 kg Rear: 90 kg	
Storage Capacity	Rear: 21.4 L	
Towing Capacity	590 kg	
Fuel Capacity	20.5 L	

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Convertible Rack System (CRS)
Winch	1,361 kg WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers, handlebar wind deflectors		

WARRANTY	
Factory	2 years



