## **©OUTLANDER™ XT-P 1000 T3B ABS**

## HIGHLIGHTS

- Rotax® V-twin engine
- Anti-Lock Braking System (ABS)
- Front and rear FOX† 1.5 PODIUM† QS3 shocks
- Continuously Variable Transmission (CVT)
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg (3,000 lbs) WARN winch with roller fairlead
- 14-in. cast-aluminum beadlock wheels
- 26-in. ITP† Terracross radial tires
- · Painted plastics for premium look
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad

- 625-W magneto
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 21.4 L (5.65 gal.) water-resistant rear compartment



Triple black / 1000

ENGINES	1000
Туре	82 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Maximum Speed	105km/h

SUSPENSIONS	
Front Suspension	Double A-arm 22.9 cm (9 in.) travel
Front Shocks	FOX 1.5 PODIUM QS3
Rear Suspension	Torsional Trailing arm Independent (TTI) 23.6 cm (9.3 in.) travel
Rear Shocks	FOX 1.5 PODIUM QS3

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
ABS	Standard

TIRES / WHEEL	. <b>S</b>
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. aluminum beadlocks

DIMENSIONS / CAPACITIES					
LxWxH	218.4 x 116.8 x 126 cm (86 x 46 x 49.5 in.)				
Wheelbase	129.5 cm (51 in.)				
Ground Clearance	27.9 cm (11 in.)				
Seat Height	87.7 cm (34.5 in.)				
Dry Weight*	361 kg				
Rack Capacity	Front: 45 kg Rear: 90 kg				
Storage Capacity	21.4L				
Towing Capacity	750 kg trailer with brakes and 335 kg trailer without brakes				
Fuel Capacity	20.5L				

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
T3B features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn, lockable fuel cap and transmission	Protection	Heavy-duty front & rear bumpers, aluminum taper profile handlebar with wind deflectors and square pad

WARRANTY		
Factory	2 years	



