©OUTLANDER™ X® mr 1000R

HIGHLIGHTS

- Rotax® V-twin engine
- Front and rear FOX[†] 1.5 PODIUM[†] QS3 shocks
- 30-in. ITP Cryptid† tires
- 14-in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- · Relocated radiator
- 1,361 kg WARN[†] winch with roller fairlead
- · Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Mudguards
- Mud-riding footrests

- 59-in. wheelbase
- Multifunction Analog / Digital gauge
- X-package coloration, graphics and seat cover



Can-Am Red & Black

ENGINE	1000R
Туре	89 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS			
Front Suspension	Double A-arm		
Front Shocks	FOX 1.5 PODIUM QS3		
Rear Suspension	Torsional Trailing arm Independent (TTI)		
Rear Shocks	FOX 1.5 PODIUM QS3		
BRAKES			
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper		

TIRES / WHEEL	.S
Front Tires	ITP Cryptid† 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid [†] 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES		
LxWxH	246 x 127 x 131 cm	
Wheelbase	149.9 cm	
Ground Clearance	33 cm	
Seat Height	93.3 cm	
Dry Weight	449 kg	
Rack Capacity	Rear: 90 kg	
Storage Capacity	Rear: 21.4 L	
Towing Capacity	590 kg	
Fuel Capacity	20.5 L	

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom	Instrumentation	Lighter type DC outlet in console, standard connecto in the back (15-A)
	bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights,	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
	fuel gauge, clock	Seat	Standard
Winch	1,361 kg WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers, aluminum taper-profile handlebar with wind deflectors and square pad, mud-riding footrests and mudguards		

WARRANTY	
Factory	2 years



