## **©OUTLANDER™ MAX LIMITED 1000R**

## HIGHLIGHTS

- Rotax® V-twin engine
- Rear Air Control Suspension (ACS) with FOX† Air Assist shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- Garmin† Montana† 650t touchscreen GPS
- 1,361 kg WARN<sup>†</sup> winch with roller fairlead
- Heavy-duty front and rear bumpers
- 14-in. cast-aluminum wheels with LIMITED finish
- 26-in. ITP<sup>†</sup> Terracross radial tires

- · Painted plastics for premium look
- Handlebar wind deflectors
- Multifunction Analog / Digital gauge
- Mudguards
- · Comfort grips



| IVIIUIII | gii | IL | DIL | 16 |
|----------|-----|----|-----|----|
| TIDEC    | ,   | v  | 1/1 | i  |

| ENGINE               | 1000R   |
|----------------------|---|
| Туре                 | 89 hp, Rotax 976 cc V-twin, liquid cooled   |
| Fuel Delivery System | Electronic Fuel Injection (EFI)   |
| Transmission         | CVT, P / R / N / H / L, standard engine braking                                     |
| Drive Train          | Selectable 2WD / 4WD with Visco-Lok <sup>‡</sup> QE auto-locking front differential |
| Power Steering       | Tri-Mode Dynamic Power Steering (DPS)   |

| SUSPENSIONS      |  |
|------------------|--|
| Front Suspension | Double A-arm<br>22.9 cm travel                             |
| Front Shocks     | Oil  |
| Rear Suspension  | Torsional Trailing arm Independent (TTI)<br>23.6 cm travel |
| Rear Shocks      | Air Control Suspension (ACS) with FOX Air Assist           |

| BRAKES |  |
|--------|--|
| Front  | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear   | Single 214 mm ventilated disc brake with hydraulic twin-piston caliper |

| TIDEO (MUIE |  |
|-------------|--|
| TIRES / WHE | ELS  |
| Front Tires | ITP Terracross 26 x 8 x 14 in.<br>(66 x 20.3 x 35.6 cm)  |
| Rear Tires  | ITP Terracross 26 x 10 x 14 in.<br>(66 x 25.4 x 35.6 cm) |
| Wheels      | 14-in. cast-aluminum with LIMITED finish                 |

| DIMENSIONS / CAPACITIES |                             |  |
|-------------------------|-----------------------------|--|
| LxWxH                   | 238.8 x 116.8 x 135 cm      |  |
| Wheelbase               | 149.9 cm                    |  |
| <b>Ground Clearance</b> | 27.9 cm                     |  |
| Seat Height             | 87.7 cm                     |  |
| Dry Weight*             | 381 kg                      |  |
| Rack Capacity           | Front: 45 kg<br>Rear: 90 kg |  |
| Storage Capacity        | Rear: 21.4 L                |  |
| Towing Capacity         | 590 kg                      |  |
| Fuel Capacity           | 20.5 L                      |  |

| <b>FEATURES</b> |  |                   |  |
|-----------------|--|-------------------|--|
| Gauge           | Multifunction Analog / Digital:<br>Speedometer, tachometer (bar graph RPM, bottom<br>bar numerical RPM), odometer, trip & hour meters,<br>diagnostic center, gear position, engine hour meter, | Instrumentation   | Integrated / removable Garmin Montana 650t touchscreen GPS, Lighter type DC outlet in console, standard connector in the back (15-A) |
|                 | 4 x 4 indicator, temperature and engine lights,<br>fuel gauge, clock   | Lighting          | 230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light   |
| Winch           | 1,361 kg WARN winch with roller fairlead   | Seat              | Convertible Rack System (CRS)  |
| Protection      | Heavy-duty front & rear bumpers,<br>handlebar wind deflectors, mudguards   | Anti-theft System | RF Digitally Encoded Security System (D.E.S.S.™)   |

## **Factory** 2 years



