©OUTLANDER™ 6X6 DPS 650 T3B

HIGHLIGHTS

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with Extra Low L-gear
- 318 kg (700 lbs) capacity Dual-Level[™] cargo box with modular accessories
- 1,361 kg (3,000 lbs) WARN winch with roller fairlead
- Tri-Mode Dynamic Power Steering (DPS)
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- Double A-arm front suspension with dive control geometry

- 12-in steel wheels
- Relocated air intakes
- · Quick release sway bar
- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- Digitally Encoded Security System (D.E.S.S.™)
- Flat bed configuration



Green / 650

ENGINES	650
Туре	62 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok‡ auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Maximum Speed	60km/h

SUSPENSIONS	
Front Suspension	Double A-arm 22.9 cm (9 in.)travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 23.6 cm (9.3 in.) travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
ABS	N/A

TIRES / WHEELS	3
Front Tires	Carlisle Badland 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle Badland 26 x 10 x 12 in (66 x 25.4 x 30.5 cm)
Wheels	12-in. steel

DIMENSIONS / CAPACITIES			
LxWxH	297 x 121 x 125.7 cm (117 x 47.6 x 49.5 in.)		
Wheelbase	208 cm (82 in.)		
Ground Clearance	27.9 cm (11 in.)		
Seat Height	87.7 cm (34.5 in.)		
Dry Weight*	489 kg		
Rack Capacity	Front: 45 kg Rear: 318 kg		
Storage Capacity	Dual-level cargo box with modular accessories Rear: 70 L		
Towing Capacity	907 kg trailer with brakes and 465 kg trailer without brakes		
Fuel Capacity	20.5 L		

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
T3B features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn, lockable fuel cap and	Protection	N/A

	1141131111331011		
WARRANTY			
Factory		2 years	





