≅RENEGADE® X® mr 1000R

HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated CVT intake and outlet
- Front and rear FOX[†] QS3 shocks
- 30-in. ITP Cryptid† tires
- 14-in. cast-aluminum beadlock wheels
- 1,361 kg WARN[†] winch with roller fairlead
- Aluminum skid plate
- · Heavy-duty front and rear bumpers
- Continuously Variable Transmission (CVT) with Extra Low L-Gear
- Aluminum taper-profile handlebar with grab handle, wind deflectors and square pad
- Tri-Mode Dynamic Power Steering (DPS™)

- Torsional Trailing arm Independent (TTI) rear suspension
- Mudguards
- Multifunction digital gauge
- · Painted plastics for premium look
- X-package coloration, graphics and seat cover



Carbon Black & Sunburst Yellow

ENGINE	1000R
Туре	89 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE [‡] auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm
Front Shocks	FOX 1.5 PODIUM QS3
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX 1.5 PODIUM QS3

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS	
Front Tires	ITP Cryptid† 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid† 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14-in. cast-aluminum beadlock

DIMENSIONS / CAPACITIES			
LxWxH	224 x 127 x 131 cm		
Wheelbase	129.5 cm		
Ground Clearance	31.8 cm		
Seat Height	93.3 cm		
Dry Weight	441 kg		
Rack Capacity	Rear: 16 kg		
Storage Capacity	N/A		
Towing Capacity	590 kg		
Fuel Capacity	20.5 L		

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
		Seat	Standard
Winch	1,361 kg WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front & rear bumpers, aluminum taper-profile handlebar with grab handle, wind deflectors and square pads, aluminum skid plate, mudguards		

WARRANTY	
Factory	2 years



