## **©OUTLANDER** PRO 570 T

## HIGHLIGHTS

- Rotax® V-Twin engine
- Intelligent Throttle Control (iTC<sup>™</sup>) with riding
- Continuously Variable Transmission (CVT) with extra low L gear
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok QE auto-locking front differential
- Tri-Mode Dynamic Power Steering (DPS)
- 26-in. Carlisle ACT HD 6-ply tires
- · Reinforced seat skin

- · Relocated air intakes
- Increased ground clearance
- Digitally Encoded Security System (D.E.S.S.)
- Multifunction digital gauge
- Steel racks with LinQ quick-attach accessory system and a combined 163 kg capacity
- 10.9 L water-resistant rear compartment



Green

ENGINES	570
Туре	48 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok $^{\ddagger}$ QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	Up to 60 km/h

Туре	48 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok <sup>‡</sup> QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	Up to 60 km/h

SUSPENSIONS	
Front Suspension	Double A-arm 22.9 cm travel
Front Shocks	0il
Rear Suspension	Torsional Trailing arm Independent (TTI) 22.4 cm travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	Carlisle <sup>†</sup> ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle <sup>†</sup> ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. steel

DIMENSIONS /	CAPACITIES
LxWxH	211 x 117 x 124 cm
Wheelbase	129.5 cm
Ground Clearance	29.2 cm
Seat Height	85.8 cm
Dry Weight*	319 kg
Rack Capacity	Front: 54.4 kg Rear: 109 kg
Storage Capacity	Rear: 10.9 L
Towing Capacity	750 kg trailer with brakes and 335 kg trailer without brakes
Fuel Capacity	20.5 L

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	70-W from dual 35-W front light / brake light
		Seat	Reinforced seat skin
Winch	Prewired for available winch	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn		

WARRANTY		
Factory	2 years	



