SOUTLANDER PRO+ 650 T

HIGHLIGHTS

- Rotax® V-twin engine
- Arched double A-arm front suspension with front sway bar
- Intelligent Throttle Control (iTC™) with riding modes
- Continuously Variable Transmission (CVT) with Extra Low L gear
- Tri-Mode Dynamic Power Steering (DPS)
- 1,361 kg (3,000 lbs) WARN[†] winch with roller fairlead
- 12-in. cast-aluminum wheels
- 26-in. 6-ply Carlisle[†] ACT HD radial tires
- Reinforced seat skin

- Relocated air intakes
- · Increased ground clearance
- Digitally Encoded Security System (D.E.S.S.™)
- High strength multi-functions racks with LinQ™ quick-attach accessory
- · 21.4 L water-resistant rear compartment
- Heated hand grips
- Mudguards



Black & Can-Am Red

ENGINES	650
Туре	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	Up to 60 km/h

SUSPENSIONS		
Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel	
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel	
Rear Shocks	Oil	

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	Carlisle† ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES		
LxWxH	218.4 x 122 x 126 cm	
Wheelbase	129.5 cm	
Ground Clearance	30.5 cm	
Seat Height	87.7 cm	
Dry Weight*	341 kg	
Rack Capacity	Front: 45 kg Rear: 90 kg	
Storage Capacity	Rear: 21.4 L	
Towing Capacity	750 kg trailer with brakes 395 kg trailer without brakes	
Fuel Capacity	20.5 L	

FEATURES			
	Multifunction Digital: Speedometer, tachometer, odometer, trip &	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Reinforced seat skin
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	Protection	Heated hand grips, mudguards

WARRANTY	
Factory	2 years

