


# 2020 OUTLANDER™ MAX PRO+ 650T

## HIGHLIGHTS

- Rotax® V-twin engine
- Arched double A-arm front suspension with front sway bar
- Intelligent Throttle Control (iTCT™) with riding modes
- Continuously Variable Transmission (CVT) with Extra Low L gear
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg (3,000 lbs) WARN® winch with roller fairlead
- 12-in. cast-aluminum wheels
- 26-in. 6-ply Carlisle® ACT HD radial tires
- Reinforced seat skin
- Relocated air intakes
- Increased ground clearance
- Digitally Encoded Security System (D.E.S.S.™)
- High strength multi-functions racks with LinQ™ quick-attach accessory
- 21.4 L water-resistant rear compartment
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards
- Heated hand grips
- Mudguards



 Black & Can-Am Red

## ENGINES

### 650

Type	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTCT™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	Up to 60km/h

## SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel
Rear Shocks	Oil

## BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

## FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	Seat	Convertible Rack System (CRS) with reinforced seat skin
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
		Protection	Heated hand grips, mudguards

## WARRANTY

Factory	2 years
---------	---------

## TIRES / WHEELS

Front Tires	Carlisle® ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle® ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

## DIMENSIONS / CAPACITIES

L x W x H	238.8 x 122 x 135 cm
Wheelbase	149.9 cm
Ground Clearance	30.5 cm
Seat Height	87.7 cm
Dry Weight*	375 kg
Rack Capacity	Front: 45 kg Rear: 90 kg
Storage Capacity	Rear: 21.4 L
Towing Capacity	750 kg trailer with brakes 395 kg trailer without brakes
Fuel Capacity	20.5 L

