©OUTLANDER™ MAX XT 650 T

HIGHLIGHTS

- Rotax® V-twin engine
- · Anti-Lock Brake System (ABS)
- Arched double A-arm front suspension with front sway bar
- Intelligent Throttle Control (iTC™) with riding modes
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg (3,000 lbs) WARN[†] winch with roller fairlead
- Heavy-duty front and rear bumpers
- · Handlebar wind deflectors
- 14-in. cast-aluminum wheels
- 26-in. ITP[†] Terracross radial tires

- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- 21.4 L water-resistant rear compartment
- Digitally Encoded Security System (D.E.S.S.™)
- Mudguards
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- · Raised floorboards



Iron Gray & Octane Blue

ENGINES	650
Туре	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	More than 60 km/h

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
ABS	Standard

TIRES / WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / C	APACITIES
LxWxH	238.8 x 122 x 135 cm
Wheelbase	149.9 cm
Ground Clearance	27.9 cm
Seat Height	87.7 cm
Dry Weight*	375 kg
Rack Capacity	Front: 45 kg Rear: 90 kg
Storage Capacity	Rear: 21.4 L
Towing Capacity	750 kg trailer with brakes 395 kg trailer without brakes
Fuel Capacity	20.5 L

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Convertible Rack System (CRS)
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	Protection	Heavy-duty front & rear bumpers, wind deflectors, mudguards

WARRANTY	
Factory	2 years

