## **SOUTLANDER** 6X6 PRO+ 650 T

## HIGHLIGHTS

- Rotax® V-Twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT)
- with extra low L-gear Tri-Mode Dynamic Power Steering (DPS)
- 318 kg capacity Dual-Level cargo box with modular accessories
- 1,361 kg (3,000 lbs) WARN winch with roller
- 26-in. Carlisle ACT HD 6-ply tires
- · 12-in. cast-aluminum wheels

- Double Torsional Trailing arm Independent (TTI2) rear suspension
- High-strength, multifunction racks with LinQ<sup>™</sup> quick-attach accessory system
- · Relocated air intakes
- Reinforced seat skin
- Digitally Encoded Security System (D.E.S.S.<sup>™</sup>)
- · Quick release rear sway bar
- Heated hand grips



Green

TIRES / WHEELS

ENGINES	650
Туре	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok QE <sup>+</sup> auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	Up to 60 km/h

INGINES	050	HINES / WHE	LLU
Туре	59 hp, Rotax 649.6 cc V-twin, liquid cooled	Front Tires	Carlisle ACT HD
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Rear Tires Carlisle ACT HD	26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking		26 x 10 x 12 in. (66 x 25.4 x 30.5
Drive Train	Selectable 4WD / 6WD with Visco-Lok QE <sup>†</sup> auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	Wheels	12-in. cast-aluminum
Speed category	Up to 60 km/h		

Arched double A-arm with front sway bar 23.3 cm travel
Oil
Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 25.1 cm travel
Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS / 0	CAPACITIES
LxWxH	297 x 122 x 126 cm
Wheelbase	208 cm
Ground Clearance	27.9 cm
Seat Height	87.7 cm
Dry Weight*	574 kg
Rack Capacity	Front: 45 kg Rear: 318 kg
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 70 L
Towing Capacity	907 kg trailer with brakes and 674 kg trailer without brakes
Fuel Capacity	20.5 L

<b>FEATURES</b>			
Gauge	Multifunction digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Reinforced seat skin
Winch	1361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	Protection	Heated hand grips

WARRANTY	
Factory	2 years

