

# 2020 OUTLANDER™ MAX 6X6 PRO+ 650 T

## HIGHLIGHTS

- Rotax® V-Twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with extra low L-gear
- Tri-Mode Dynamic Power Steering (DPS)
- 318 kg capacity Dual-Level cargo box with modular accessories
- 1,361 kg (3,000 lbs) WARN winch with roller fairlead
- 26-in. Carlisle ACT HD 6-ply tires
- 12-in. cast-aluminum wheels
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- Relocated air intakes
- Reinforced seat skin
- Digitally Encoded Security System (D.E.S.S.™)
- Quick release rear sway bar
- Heated hand grips
- Dynamic passenger comfort ergonomics



Green

## ENGINES

### 650

Type	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok <sup>®</sup> QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	Up to 60 km/h

## SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 25.1 cm travel
Rear Shocks	Oil

## BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

## FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	Seat	Reinforced seat skin
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
		Protection	Heated hand grips

## WARRANTY

Factory	2 years
---------	---------

## TIRES / WHEELS

Front Tires	Carlisle ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

## DIMENSIONS / CAPACITIES

L x W x H	317 x 122 x 141 cm
Wheelbase	228 cm
Ground Clearance	27.9 cm
Seat Height	87.7 cm
Dry Weight*	595 kg
Rack Capacity	Front: 45 kg Rear: 318 kg
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 70 L
Towing Capacity	907 kg trailer with brakes and 674 kg trailer without brakes
Fuel Capacity	20.5 L

