§MAVERICK™ TRAIL 800 T

HIGHLIGHTS

AGILE

- Sturdy engine and transmission
- Easy Handling and capabilities
- Front and rear suspension designed for trail riding

ADVENTUROUS

- Meaningful functionality and versatility
- Enhanced comfort with Ergo Lok cockpit
- Build your Maverick Trail that fits your needs

CONFIDENT

- Can-Am design and proven fit & finish
- Enhanced protection
- More adventure and less maintenance

SPECIFIC TO PACKAGE

- Visco-Lok‡ auto-locking front differential
- 12-in. steel wheels
- Ergoprint seats



White

ENGINES	800
Туре	55 hp, Rotax® 799.9 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Visco-Lok [†] auto-locking front differential
Driving Assistance	Electronic Hill Descent Control
Power Steering	N/A
Speed category	Up to 60 km/h

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar 25.4 cm travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with sway bar 26.7 cm travel
Rear Shocks	Twin tube gas charged shocks

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEEL	S
Front Tires	Carlisle ACT
	26 x 8 x 12 in.
	(66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT
	26 x 9 x 12 in.
	(66 x 22.9 x 30.5 cm)
Wheels	12-in. steel
DIMENSIONS /	CAPACITIES
DIMITIONS /	UAFACITIES

DIMENSIONS /	CAPACITIES
LxWxH	300.5 x 157.8 cm x 175.5 cm
Wheelbase	230.1 cm
Ground Clearance	25.4 cm
Dry Weight	596 kg
Cage	ROPS-approved profiled cage Certified ISO 3471
Cargo Box Capacity	136 kg
Storage Capacity	Total: 20.2 L Glove Box: 15.6 L Driver storage: 1.5 L Center console and Cup holders: 3.1 L
Towing capacity	680 kg
Fuel Capacity	38 L

FEATURES				
Gauge	7.6 in. (19.3 cm) wide digital display with keypad	Winch	Prewired for available winch	
		Steering Wheel	Adjustable tilt steering	
Instrumentation	tion Lighter type DC outlet in console (20-A) Protection		Integrated front steel bumper, injected full body skid	
Magneto	650W		plates, mudguards, mudflaps	
Lighting	Two 55 W reflectors and LED tail lights	Hitch Type	2-in. hitch receiver with tow ball, 7-pin trailer connection (12V)	
T-category features	Horn, flashers and position lamps, mirrors, hook on front metal bumper			

WARRANTY		
Factory	2 years	

