§TRAXTER X™ mr HD10

HIGHLIGHTS

PLATFORM FEATURES

- 211.5 cm wheelbase
- 38 cm of ground clearance
- Dynamic Power Steering (DPS™) ECO™ / ECO Off / Work modes
- 1,134 kg towing capacity Multi-function cargo box with LinQ easy installation
- accessories Rear differential with Turf mode

SPECIFIC TO X mr PACKAGE

- 162.5 cm wide with Arched A-arm
- Smart-Lok front differential™*
- Strategically positioned engine air intake and CVT inlet / outlet
- 14-in. cast-aluminum wheels
- VERSA-PRO bench seat with bolster seats, reinforced seat skin featuring X package trims and adjustable driver seat
- HMWPE full skid plate
- 2,014 kg winch with synthetic rope
- Heavy-duty front steel bumper
- Full hard roof
- Aluminum rock slider
- 7.6 in. digital display with keypad
- Brake holding mechanism

Heavy-duty Rotax® engine

TOUGH

- Smooth, durable and responsive transmission
- True Can-Am DNA with a strong identity
- **CAPABLE**
- Work or ride with confidence
- Meaningful and versatile functionality
- Easy handling and capabilities

CLEVER

- Advanced comfort and intuitive cockpit with optimized visibility
- Multifunction cargo box with sturdy tailgate and smart storage
- 1-year maintenance free and easy access to key maintenance components





Iron Gray & Manta Green / HD10

			
ENGINE	HD10		
Туре	82 hp, Rotax® 976 cc, V-twin, liquid cooled with strategically positioned engine air intake		
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	PRO-TORQ Transmission with Quick Response System (QRS), Electronic Drive Belt Protection, lower gearing ratio and high airflow ventilation with strategically positioned CVT air intake and exhaust Extra-L/H/N/R/P		
Drive Train	Selectable Turf Mode / 2WD / 4WD TRAIL / 4WD MUD with exclusive Smart- Lok** technology.		
	**Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry		
Driving Assistance	Electronic Hill Descent Control / ECO / ECO Off / Work modes		
Power Steering	Dynamic Power Steering (DPS)		
SUSPENSIONS			
Front Suspension	Arched double A-arm with sway bar / 25.4 cm travel		
Front Shocks	Twin tube gas charged shocks		
Rear Suspension	Arched TTA with external sway bar / 25.4 cm travel		
Rear Shocks	Twin tube gas charged shocks		
BRAKES			
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Dual 220 mm ventilated disc brakes with hydraulic single-piston calipers		

DIMENSIONS /	CAPACITIES			
LxWxH	328.6 x 162.5 x 208.3 cm			
Wheelbase	211.5 cm			
Ground Clearance	38.1 cm			
Estimated Dry Weight	770 kg			
Cage	Profiled cage ROPS approved			
Cargo Box Dimensions	96.5 x 138.4 x 30.5 cm			
Cargo Box Capacity	454 kg			
Tailgate Load Capacity	113.4 kg			
Storage Capacity	Total: 61.3 L Under dash: 22.8 L Waterproof and removable box under passenger seat: 21 L Dash: 7.7 L Water-resistant and removable toolbox: 6.3 L Armrests and cup holders: 3.5 L			
Towing Capacity	1,134 kg			
Payload Capacity	680 kg			
Fuel Capacity	40 L			
Person Capacity	3			

TIRES / WHEELS	
Front Tires	ITP†* Cryptid† 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	ITP* Cryptid 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum

Brake holding mechanism

FEATURES			
Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO / ECO Off / Work modes, seat belt, diagnostics, clock, battery voltage, engine temperature	Seat	VERSA-PRO bench seat with bolster seats for additional lateral support, passenger seats flipping up, adjustable driver seat, underside hooks, reinforced seat skin featuring X package trims and contoured bench to improve entrance /exit of the cab
Lighting	140 W lighting output from four 35-W reflectors ensuring a wide visiblity and LED tail lights	Winch	Relocated 2,041 kg winch with synthetic rope and aluminum fairlead
Instrumentation	Two lighter type DC outlets, one in the console (20-A) and one in the under dash storage (20-A)	Protection	Heavy-duty front steel bumper, HMWPE full skid plate, aluminum rock sliders, mudguards
Magneto	650 W	Hitch Type	2-in. hitch receiver
Battery	12 V (30 amp/h)	Steering Wheel	Adjustable tilt steering

Factory 2 years



