

## HIGHLIGHTS

| Indifficients        |  |                |
|----------------------|--|----------------|
| AGILE                | Sturdy engine and transmission     Easy Handling and capabilities     Front and rear suspension designed for trail rid   | ling           |
| ADVENTUROUS          | <ul> <li>Meaningful functionalities and versatilities</li> <li>Enhanced comfort with Ergo-Lok cockpit</li> <li>Build your Maverick Trail that fits your needs</li> </ul>   |                |
| CONFIDENT            | <ul> <li>Can-Am design and proven fit &amp; finish</li> <li>Enhanced protection</li> <li>More adventure and less maintenance</li> </ul>  |                |
| PLATFORM<br>FEATURES | <ul> <li>62.8 in. (159.6 cm) wide</li> <li>90.6 in. (230.1 cm) wheelbase</li> <li>10 in. (25.4 cm) of ground clearance</li> <li>Up to 10.5 in. (26.7 cm) suspension travel</li> <li>7.6 in. (19.3 cm) wide digital display with keypare</li> <li>SPORT / ECO<sup>TM</sup> modes</li> <li>Ergoprint seats</li> <li>Net (instead of doors)</li> <li>RF key DESS with Start / Stop button</li> <li>Mudguard and Mudflap</li> <li>Rear hitch and tow ball</li> <li>7-pin trailer connexion (12V)</li> <li>LED tail lights with halo glow effect</li> <li>Horn, flashers and position lamps, left/right min plate support, hook on front metal bumper, driv detector, Low brake fluid sensor</li> </ul> | rrors, license |



1,256 lb (569.7 kg)

Profiled cage

## ENGINE

Wheels

BRAKES Front

Rear

| 39 kW (52 hp) / 41 lb-ft, Rotax® ACE (Advanced<br>Combustion Efficiency) 650 cc single cylinder,<br>liquid cooled, with catalytic converter |
|---|
| Intelligent Throttle Control (iTC <sup>™</sup> ) with<br>Electronic Fuel Injection (EFI)  |
| PDrive primary CVT with engine braking and<br>Electronic Drive Belt Protection<br>L / H / N / R / P   |
| Selectable 2WD / 4WD with Visco-Lok† auto-<br>locking front differential  |
| Electronic Hill Descent Control<br>SPORT / ECO™ modes   |
| N/A   |
|   |
| Double A-arm with sway bar / 10 in. (25.4 cm)<br>travel   |
| Twin tube gas charged shocks  |
| TTA with sway bar / 10.5 in. (26.7 cm) travel   |
| Twin tube gas charged shocks  |
|   |
| Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)  |
| Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)  |
|   |

| -                  | ROPS approved   |  |
|--------------------|---|--|
| LxWxH              | 118 x 62.8 x 69 in.   |  |
|                    | (300.5 x 159.6 x 175.3 cm)  |  |
| Wheelbase          | 90.6 in. (230.1 cm)   |  |
| Ground Clearance   | 10 in. (25.4 cm)  |  |
| Cargo Box Capacity | 300 lb (136 kg)   |  |
| Towing Capacity    | 1,500 lb (682 kg)   |  |
| Storage Capacity   | Total: 5.3 gal (20.2 L)<br>Glove Box: 4.1 gal (15.6 L)<br>Driver storage: 0.4 gal (1.5 L)<br>Center console and Cup holders: 0.8 gal (3.1 L)  |  |
| Fuel Capacity      | 10 gal (38 L)   |  |
|                    |   |  |
| FEATURES           |   |  |
| Gauge              | 7.6 in. (19.3 cm) wide digital display with<br>keypad, Speedometer, tachometer, odometer,<br>trips and hour meters, fuel, gear position,<br>SPORT / ECO™ mode, seat belt and 4 x 4<br>indicator, front and rear diff lock indicators,<br>diagnostics, clock, battery voltage, engine<br>temperature |  |
| Instrumentation    | Lighter type DC outlet in console (20-A)  |  |
| Anti-theft System  | RF Digitally Encoded Security System<br>(D.E.S.S.™) with Start / Stop button  |  |
| Magneto            | 650-W   |  |
| Lighting           | Two 55 W reflectors and LED tail lights with<br>halo glow effect  |  |
| Winch              | N/A   |  |
| Steering Wheel     | Adjustable tilt steering  |  |
| Protection         | Integrated front steel bumper, Full skid plate<br>Mudguard and Mudflap  |  |
| Hitch Type         | 2 in. hitch receiver with rear hitch and tow ball   |  |

## WARRANTY

Factory warranty

DIMENSIONS / CAPACITIES Estimated Dry Weight \*

Chassis / Cage

2-year BRP limited warranty

©2021 Bombardier Recreational Products Inc (BRP). All rights reserved, <sup>TM</sup>, \* and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. \*Base model dry weight shown. \*Visco-Lok is a trademark of GKN Viscodrive GmbH. 'All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that triding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

12 in. (30.5 cm) steel

Dual 220 mm disc brakes with hydraulic twin-piston calipers Dual 220 mm disc brakes with

hydraulic twin-piston calipers

