

RYKER

PACKAGE HIGHLIGHTS

- Priced to excite
- Designed for fun
- Easy to ride
- 100 000 ways to make it your own



SHOWN WITH INTENSE BLACK PANELS

	Rotax® 600 ACE™	Rotax® 900 ACE™
ENGINE		
Type	Rotax® 600 ACE™ in-line 2 cylinders, liquid-cooled with electronic fuel injection and electronic throttle control	Rotax® 900 ACE™ in-line 3 cylinders, liquid-cooled with electronic fuel injection and electronic throttle control
Bore & stroke	74 x 69,7 mm (2.9 x 2.7 in.)	74 x 69,7 mm (2.9 x 2.7 in.)
Power	50 hp (37.3 kW) @ 7300 RPM	82 hp (61.1 kW) @ 8000 RPM
Torque	49.7 Nm (36.7 ft-lb) @ 6000 RPM	79.1 Nm (58.3 ft-lb) @ 6500 RPM
CO2 emissions	127 g/km	143 g/km
Fuel consumption	5.4 l/100 km (43.6 mpg)	6.08 l/100 km (38.7 mpg)
TRANSMISSION		
Type	Automatic (CVT) with reverse function	
CHASSIS		
Front suspension	Double wishbone	
Front shocks type / travel	SACHS† Twin-tube coil-over shocks / 136 mm (5.35 in.)	
Rear suspension	Multi-link - mono swing arm	
Rear shocks type / travel	SACHS† Twin-tube coil-over shocks with preload adjustment / 145 mm (5.71 in.)	
Electronic brake distribution system	Foot-operated, hydraulic 3-wheel brake	
Front brakes	270 mm discs with Nissin 2-piston floating calipers	
Rear brake	220 mm disc, 1-piston floating caliper	
Parking brake	Park lock	
Front tires	MC 145/60R16 66T	
Rear tire	MC 205/45R16 77T	
Aluminum front rims	5-spoke Carbon black, 406 x 114 mm (16 x 4.5 in.)	
Aluminum rear rim	5-spoke Carbon black, 406 x 165 mm (16 x 6.5 in.)	
CAPACITY		
Rider capacity	1	
Maximum vehicle load	204 kg (449.7 lb)	
Storage capacity	7 L (1.85 gal)	
Fuel capacity	20 L (5.28 gal)	
Fuel Type	Premium unleaded	

	Rotax® 600 ACE™	Rotax® 900 ACE™
DIMENSIONS		
L x W x H	2,352 x 1,522 x 1,063 mm (92.6 x 59.9 x 41.9 in.)	2,352 x 1,522 x 1,060 mm (92.6 x 59.9 x 41.7 in.)
Wheelbase	1,709 mm (67.3 in.)	
Seat height	599 mm (23.6 in.)	597 mm (23.5 in.)
Ground clearance	97 mm (3.8 in.)	
Dry weight	270 kg (594 lb)	280 kg (616 lb)
INSTRUMENTATION		
Type	4.5" digital display	
Main Functions	Speedometer, tachometer, odometer, trips, distance to empty, engine lights, fuel gauge and clock	Speedometer, tachometer, odometer, trips, distance to empty, engine lights, fuel gauge, clock, ECO mode and Sport mode
SAFETY & SECURITY		
SCS	Stability Control System	
TCS	Traction Control System	
ABS	Anti-lock Braking System	
Anti-theft system	Digitally Encoded Security System (D.E.S.S.™)	
HHC	Hill Hold Control	
COVERAGE		
Factory Warranty	2-year BRP Limited Warranty	
Roadside Assistance	2-year roadside assistance provided by Allianz Assistance, world leader in Automotive and Travel assistance, on behalf of BRP.	
FEATURES		
	2 halogen headlamps (55-W) Front fenders with integrated LED lights Dual USB port Glove box Adaptive foam waterproof seat	

**Only on Rotax 900 ACE Engine option

CLASSIC SERIES¹



EPIC SERIES



EXCLUSIVE SERIES²



NEW PANELS



FEATURE HIGHLIGHTS



AUTOMATIC TRANSMISSION (CVT)
No need to worry about changing gears as your continuously variable transmission will find the perfect combination of performance and fuel efficiency for you.



ENGINE OPTIONS
The 2-cylinder Rotax 600 ACE is the ultimate in accessible performance, while the 3-cylinder Rotax 900 ACE is the power & excitement standard of choice!



DRIVESHAFT
Highly durable and robust driveshaft technology will help you enjoy a smooth ride all along the way. No need for further adjustment, alignment or maintenance.



UFIT
Can be adjusted tool-free to fit the rider and provide a personalized and comfortable riding experience.



VSS
Vehicle Stability System that uses a variety of technologies, including SCS / ABS / TCS, to monitor the vehicle and keep the rider confident on the road.



CUSTOMIZATION
The Can-Am Ryker was engineered to be almost infinitely customizable with 1 or 2-up options! Mere moments are all it takes to give it a transformation.

¹Choice of one set of Classic Panels included at the vehicle purchase. ²Exclusive Panel Kits are available in limited quantities.

©2021 Bombardier Recreational Products Inc., (BRP). All rights reserved. "R" and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models depicted may include optional equipment. Vehicle performance may vary depending on weather, temperature, altitude, riding ability and rider/passenger's weight.